

Cont  
A1  
adhesive 206 in selected areas there between as generally illustrated in Figures 11 and 12. The first layer 202 of the mailing assembly 200 includes a return postcard 208 with an incorporated designator section 210. At each end of the return postcard 208 are anchor portions 212,214 separable by perforated tear lines 216,217, respectively. On a back side of each of the anchor portions 212,214 is the adhesive 206. The adhesive 206 provides for attachment of the first layer 202 to the second layer 204 and following removal of the first layer 202 from the second layer 204, the adhesive 206 beneath the anchor portions 212,214 allows for attachment of the first layer 202 to a mailpiece. An auxiliary label 218 is provided exterior to the anchor portion 212 and has the adhesive 206 on its back side. As a result, the auxiliary label 218 may be implemented as described with references to Figures 7-9.

---

Please replace the first full paragraph on page 10, which may also be identified as the fourth paragraph of the DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS with the following paragraph:

---

A2  
The assembly 10 also has a front bottom portion 18 that includes the return receipt postcard 13 that can be similar to United States Postal Service form PS-3811. The return receipt postcard 13 may include a set of instructions 20 for the sender, as well as an article addressee section 22 for pre-printing the